

S-202 SDT Adhesive for Static Dissipative Tile



CAUTION

S-202 **EYE AND SKIN IRRITANT**

STIR WELL BEFORE USING.

For use with the following Installation

System:

- Static Dissipative Tile (SDT)

DESCRIPTION:

Type:	Water-based resin
Color:	Black
Taggants:	None
Trowel:	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel with S-894 Fine Notch Blade Fine notch (1/32" deep, 1/16" wide, 5/64" apart), U-notch
Coverage:	Approximately 150 sq. ft./gal. (14 sq. m)
Units:	1 gallon (3.78 L) and 4 gallons (15.14 L)
Shelf Life:	12 months, unopened
Freeze/Thaw Stable:	No, keep from freezing
VOC Content:	< 50 g/L; calculated and reported, SCAQMD 1168
Open Time:	Until dry to touch, 60 minutes or more
Working Time:	Up to 6 hours (May vary based on job conditions, substrates, temperature, and humidity)
Clean Up:	Wet or Dry — clean, white cloth and mineral spirits
Subfloors:	All grade levels of concrete and suspended wood Ceramic, terrazzo, polymeric poured and certain metal subfloors when properly prepared with S-194 Radiant Heated subfloors where the surface temperature does not exceed 85° F (29° C)
Advantages:	Moisture and alkali resistant Long working time (up to 6 hours)