

S-580 Flash Cove Adhesive



CAUTION

S-580 **EYE AND SKIN IRRITANT**

STIR WELL BEFORE USING.

For use with the following Installation Systems:

- Commercial Vinyl-Backed
- Commercial Heterogeneous and Inlaid
- Residential Felt-Backed
- Commercial/Residential Linoleum Sheet
- Fiberglass-Reinforced Sheet (Full spread application)
- ToughGuard II

DESCRIPTION:

Type:	Water-based/resin; pressure-sensitive; acrylic base
Color:	White
Taggants:	Contains no visible taggants
Applicator:	Brush or roller
Coverage:	200–250 sq. ft./ half-gallon (18–23 sq. m)
Units:	Half-gallon (1.89 L)
Open Time:	Dry to pressure sensitive state; minimum of 20–30 minutes
Working Time:	Unlimited (May vary based on job conditions, temperature, humidity, air circulation, etc.)
Shelf Life:	1 year, unopened
Freeze/Thaw Stable:	Yes, to 10° F (-12° C)
VOC Content:	Zero g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet — clean, white cloth with neutral detergent and water Dry — clean, white cloth and mineral spirits
Walls:	Standard, structurally sound
Advantages:	Moisture and alkali resistant Excellent grab AGIS Guarantee Nonflammable, ammonia-free and low odor Contains low or no organic solvents